



AB-151 Scrim

HVAC/Construction Scrim

AB-15-Scrim is an all purpose self-adhering fiberglass ductwork scrim primarily used for temporary fixation of ductwork prior to sealant application. For use with UL 181 Listed applications.

TECHNICAL DATA

Average net weight.....1.6 (oz./yd²)
Cross directional strength.....104.8 (lbs./in.)
Treatment % on fabric.....22.5%
Thread Count (per inch of width)
 Warp threads9
 Filling threads9
Thicknes007 in.
Packaging.....3" X 150"; 18 rolls per case

AB-151 Scrim PART NUMBER

1 Case w/ (10) 3" x 150' Rolls310553

APPLICATION

Temperature 35°F. to 110°F. (1.7°C. to 44°C.)
Method Cut desired length, peel off release liner, apply. Overlap at ends. Rub down with heavy pressure to assure complete contact.
Preparation..... Surface must be clean and dry, oil and grease free.
Clean Up UN-TACK™ or Solvent (Use safe handling practices.)
Painting..... Use paint appropriate for aluminum.

STORAGE

Temperature 35°F. to 110°F. (1.7°C to 44°C)
Shelf Life..... 24 months
Flammability..... Non-flammable

PRECAUTIONS

Surface must be clean and free of moisture, contamination and foreign matter. Do not allow this product to freeze. Do not apply this when rain or freezing temperatures will occur within 36 hours. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach of children. Review MSDS for complete safety information prior to use. DO NOT use where acidic or alkaline chemicals are present (ie., lab fume hood, vents, etc.)

For Industrial Professional Use Only.

For additional information contact:



900 Hensley Lane
Wylie, Texas 75098
Phone: (800) 527-7092 FAX: (972) 442-0076
www.hardcast.com