



PART NUMBERS

308585	1 5-Gallon Pail (Black)
308587	1 50-Gallon Drum (Black)

TECHNICAL DATA

Color	Gray (wet), Black (dry)
Consistency	Low-viscosity liquid
Base	Synthetic latex
Solvent	Water
Weight per Gallon	10.0 lbs (+/- 0.2)
Solids Content	53% (+/-2)
Viscosity	8,500–9,500 cps
Coverage	Up to 530 sq ft/gal (sprayed)
Initial Bonding Time	10 minutes* (5 mils @ RT)
Dry Time	20 minutes* (5 mils @ RT)
Service Temperature	-20°F to 200°F
Water Resistance	Good
Mildew Resistance	Mold and mildew resistant
VOC	42.2 g/l (less water)
Packaging	5-gal pail, 50-gal drum
Freeze/Thaw Stability	Passed 5 cycles
Specification Compliance	Passed ASTM C916, LEED Compliant SCAQMD Rule 1168

**For optimal coverage, see Application Instruction Sheet, cylinder back label or cylinder shipping carton back label.*

PRECAUTIONS

Inspect all winter shipments upon arrival. Apply when temperatures will not fall below freezing. Do not apply this product in weather- exposed areas or where temperatures will exceed 160°F. Keep out of the reach of children. Review Material Safety Data Sheet for safety information prior to use.

For Industrial Professional Use Only.

BOOTH-TACK is a quick-tack, nonflammable, water-based insulation adhesive engineered for spray booth applications. BOOTH-TACK is used in situations when duct insulation is promptly secured by an insulation fastener or the duct section is stored horizontally until the adhesive is dry. BOOTH-TACK offers high strength, low viscosity, great coverage and low suspended solids.

APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Method	For use in spray booth operations or specific areas. BOOTH-TACK may be brush- or roller-applied to secure insulation to the substrate. Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil and grease.
Clean Up	UN-TACK™ or Solvent (Use safe handling practices)

STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C)
Shelf Life	One year (unopened)
Flammability	Non-flammable

CLASSIFIED
UL
US

UNDERWRITERS LABORATORIES, INC.®
CLASSIFIED ADHESIVE
Surface Burning Characteristics 294U
*Applied to inorganic reinforced cement board

FLAME SPREAD..... 0
SMOKE DEVELOPED..... 0

*Tested as applied in two 3" (76.2 mm)-wide strips 8" (203.2 mm) on center at a coverage of 530 sq ft/gal (13 sq M/L). Flash point of finished adhesive, closed cup: no flash to boiling.

City of Los Angeles Approval RR #8069