



### PART NUMBERS

308609	1 Case w/4 1-Gallon Pails (White)
308608	1 5-Gallon Pail (White)
318903	1 Case w/4 1-Gallon Pails (Black)
318902	1 5-Gallon Pail (Black)

### TECHNICAL DATA

Color	White & Black
Consistency	Medium Viscosity Sealant
Base	Synthetic latex
Solvent	Water
Weight per Gallon	10.0 lbs. (+/- 0.5)
Solids Content	52 % (+/- 2%)
Viscosity	10,000 – 20,000 cps
Coverage	Up to 200 sq ft/gal
Flexibility	Excellent
Dry Time (to touch)	30 minutes*
Service Temperature	10°F to 200°F
Surface Burning	Flame spread 10, Smoke developed 40, (When tested in accordance with ASTM E84)
Weather Resistance	Excellent
Mildew Resistance	Mold & Mildew resistant
VOC	>20 g/l (less water)
Packaging	1 gal. & 5 gal. pails
Specifications Compliance	Passes SCAQMD Rule 1168

### APPLICATION

Temperature	35°F to 110°F (1.7°C to 44°C)
Method	Apply with a brush or roller to coat and seal cut edges of fiberglass and foam insulation. Apply according to SMACNA specifications and local codes.
Preparation	Surface must be dry and free of dirt, oil and grease.
Clean Up Wet	Soap and Water
Clean Up Dry	UN-TACK™ or Solvent (Use safe handling practices)
Painting	Only latex or epoxy paints

SEAL-TACK is engineered to seal cut ends of fibrous glass duct liner and to coat foam insulation. It provides exceptional vapor barrier characteristics for liquid chiller piping insulation applications. SEAL-TACK's exceptional strength and weather resistance provide application flexibility for both indoor and outdoor use.

### STORAGE

Temperature	35°F to 110°F (1.7°C to 44°C)
Shelf Life	One year (unopened)
Flammability	Non-flammable

### PRECAUTIONS

Inspect all winter shipments upon arrival. Do not allow this product to freeze. Apply when temperatures will not fall below freezing for the next 36-48 hours. Do not apply this product where temperatures will exceed 200°F. Keep out of the reach children. Review Material Safety Data Sheet for complete safety information prior to use.

**CAUTION: HARMFUL IF SWALLOWED OR INHALED.** Avoid breathing vapors. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. If swallowed, DO NOT INDUCE VOMITING. Call a physician. Overexposure to vapors may cause respiratory irritation. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Contact a physician immediately.

**MAY CAUSE SKIN IRRITATION:** Prolonged or repeated contact may cause drying, brittleness, cracking or irritation. Use of impervious gloves and clothing recommended. Avoid contact with skin. May be irritating to sensitive skin. Wash thoroughly after handling. In case of contact with skin, remove contaminated clothing and thoroughly wash affected area with soap and water. Do not use if skin is broken. If rash develops, discontinue use. Contact a physician if symptoms persist. REVIEW MATERIAL SAFETY DATA SHEET FOR COMPLETE SAFETY INFORMATION PRIOR TO USE.

CONTAINS: ETHYLENE GLYCOL and AMMONIA.

MAY NOT BE REPACKAGED or sold for other than industrial or professional use.

KEEP OUT OF REACH OF CHILDREN.

**For Industrial Professional Use Only.**