

# MULTI-BLADE DAMPER HARDWARE

Hardcast Hardware

## OPPO-LINK BRACKET

For Opposed-Action Dampers



**OPPO-LINK low bracket rods are fully threaded into the brass pivots. They cannot work loose!**

Part #	Product Description	Qty
307937	OPPO-LINK BRKT LOW 6" ROD (OLL-14-6)	100/Case
307946	OPPO-LINK BRKT LOW SSSL 6" ROD (OLL-146-SS)	25/Case
307940	OPPO-LINK BRKT LOW 8" ROD (OLL-14-8)	100/Case
307948	OPPO-LINK BRKT LOW SSSL 8" ROD (OLL-148-SS)	25/Case



- 16-Gauge Steel Precision Stamping, Zinc Plated
- Material's Narrow, Efficient Design Gives Same Lateral Adjustment as Other Hardware Models
- Brass Pivot Is Tapped to Receive the Threaded End of the Connecting Rod. IT CAN NEVER PULL OUT! *Standard 8" Rod Length Accommodates Wide Blades. Special 6" Rod Length Available for Narrow Blades*
- USED WITH PARA-LINK (HI) BRACKET FOR ALL OPPOSED-ACTION DAMPERS
- Uses One High and One Low Bracket
- Self Adjusting
- Heavy-Duty "Low" Steel Stamping Has "Clipped" Forward Edge to Clear Opposing Blade When Necessary
- Narrower "Low" Bracket Offers Same Lateral Play as Other Hardware Models and Features Less Air Resistance
- Connecting Link Rod (1/4" Diameter) Is Threaded into Its Brass Pivot and Can Never Pull Out
- Same Compression Ring/Locknut Principle Guarantees Easy Adjustment and Firm Clamping of Rod to the High Bracket



**Also Available in Stainless Steel**



Part #	Product Description	Qty
308071	PIVOT BRKT LOW 1/4" TAP & SET SCREW (LBP-14)	100/Case