

KWIK-STIK GASKET TAPE

For Access Doors and Dampers



KWIK-STIK is a superior-quality, self-stick gasket tape material. The neoprene and urethane products offered have been on the market for many years and have met the test of time. The adhesives used have been chosen for their dependability, holding power and wide temperature range.

NEOPRENE GASKET

Closed-cell, medium-density neoprene sponge meets all standards for use on Access Doors in high-velocity installations. It can be used on blade edges of multi-blade dampers and similar applications where airtightness and insulation qualities are needed.

Product Technical Data

Operating Temperature Range:
-30° to 200°F (-35° to 94°C)

Self-adhesive, peel-off backing offers high tack adhesion to metal surfaces. Adhesion improves with time. Metal should be clean and free of grease and oils.

Part #	Description	Neoprene Thickness	Width	Length/Rt	Qty
304605	GSKT TAPE NEO 1/8" X 1/2" X 50' (KGN-22)	1/8"	1/2"	50'	24/Case
304606	GSKT TAPE NEO 1/8" X 3/4" X 50' (KGN-23)	1/8"	3/4"	50'	16/Case
304607	GSKT TAPE NEO 1/4" X 3/4" X 25' (KGN-43)	1/4"	3/4"	25'	16/Case
304608	GSKT TAPE NEO 3/8" X 3/4" X 20' (KGN-63)	3/8"	3/4"	20'	16/Case

URETHANE GASKET

Polyurethane foam (polyester) is backed with a dependable high-tack adhesive with peel-off paper backing. This economical foam tape is a prominent tool known for its lightness, resilience and resistance to oils, moisture and many chemicals encountered in HVAC applications.

Product Technical Data

Operating Temperature Range:
-50° to 180°F (-45° to 82°C)

Part #	Description	Polyurethane Thickness	Width	Length/Rt	Qty
304609	GSKT TAPE URETHANE 3/16" X 1/2" X 50' (KGU-38)	3/16"	1/2"	50'	24/Case
304610	GSKT TAPE URETHANE 1/4" X 3/4" X 40' (KGU-43)	1/4"	3/4"	40'	16/Case
304611	GSKT TAPE URETHANE 3/8" X 3/4" X 25' (KGU-63)	3/8"	3/4"	25'	16/Case